


# Improved Performance in Waterborne Wood Coatings

The waterborne additives and rheology modifiers from Elementis, an industry leader in innovation and sustainability provide the right solutions to maintain the coatings performance when changing from solvent base to waterborne wood coatings. Our application labs and technical experts are at your service to prove the benefits in your formulation.

RHEOLATE® nonionic synthetic associative thickeners provide coatings with good rheological behavior which leads to an excellent balance in thickening, flow, & leveling, with minimal effect on film gloss. BENTONE® rheological additives based on hectorite clays have the ability to thicken aqueous systems, provide excellent in-can stability and sag control for a wide range of coating formulations. NUOSPERSER® and SUPREAD® wetting and dispersing agents provide good application performance for inorganic, organic and carbon black pigments. They are widely compatible with many coating formulas imparting lower foaming and improved stability. DAPRO® antifoaming and defoaming agents are effective in both the grinding and the letdown stages of a wide range of coating systems.



## Performance System for Waterborne Wood Coatings

Product name	Product type	Composition	Description
RHEOLATE® 299	Rheological additives	Nonionic synthetic associative thickeners	Provide low shear viscosity build, highly efficient thickener and excellent sag resistance. Ideal for spray applied coatings.
RHEOLATE® FX 1010			Increase mid & high shear viscosity, improves anti-settling properties, reduces roller spattering, <b>almost no side effect on film gloss and transparency</b>
RHEOLATE® HX-6008			Efficient high shear viscosity build in water-borne systems with some mid-shear viscosity contribution, without sacrificing flow and leveling.
RHEOLATE® 350D			Provide high-shear viscosity, excellent flow and leveling properties, improve film-build and hiding power, <b>good color acceptance and stability.</b>
BENTONE® DE	Rheological additives	Hectorite	It is a refined natural hectorite clay modified for easy dispersion. It allows for high pre-gel solids (up to 14 %) with pourable viscosity. It provides excellent in-can stability and sag control for a wide range of coating formulations.
BENTONE® DY CE			Efficient low & mid shear thickener, provide good suspension and sag control, improve in-can stability and anti-syneresis, <b>good water resistance.</b>
BENTONE® LT			Highly efficient thickener and thixotropic flow, excellent in-can stability and sag control, reduces syneresis.
NUOSPERSER® FX 7500W	Wetting and dispersing agents	Polymeric dispersant	Excellent wetting and dispersing for organic, inorganic and carbon black pigments. Good color development, gloss, levelling and hiding power. Good stability and deflocculating behavior, low foam creation. Also good performance in general pigment concentrates
SUPREAD® 2059	Wetting agents	Surface Tension Modifier	Silicone free, super wetting agent for aqueous system, fast dynamic surface wetting, low foaming, low impact on paint rheology, no recoatability and blocking issues.
SLIP-AYD® FS 444	Slip and leveling additives	Modified polysiloxane	A liquid additive for increasing surface slip and mar resistance, exhibits good compatibility with minimum side effects.
DAPRO® DF 677	Defoamers	Silicone emulsion	Effective defoamer, provides excellent anti-foaming and de-foaming with good compatibility.

Elementis.com/Coatings/Performance-Series

North America  
469 Old Trenton Road, East Windsor, NJ 08512,

Europe  
c/o Elementis GmbH, Stolberger Strasse 370, 50933 Cologne, Germany

Asia  
99, Lianyang Road, Songjiang Industrial Zone, Shanghai, China 201613